



**Material Safety Data Sheet**  
Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Aug-27-2012

Revision Date Aug-27-2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product code** **IMS201**  
**Product name** **Premium Graphic Screen Wash**  
**Product category** ImageStar®

**Manufacturer or supplier's details**

UNITED STATES  
 Nazdar Company  
 8501 Hedge Lane Terrace  
 Shawnee, KS 66227  
 Tel: 1-913-422-1888  
 Tel: 1-800-677-4657  
 Fax: 1-913-422-2294

UNITED KINGDOM  
 Nazdar Limited  
 Barton Road  
 Heaton Mersey  
 Stockport, England SK4 3EG  
 Tel: +44 161 442 2111

**Emergency Telephone Number**

USA: Chemtrec: 1-800-424-9300  
 Outside USA: Chemtrec: 1-703-527-3887

Website: [www.nazdar.com](http://www.nazdar.com)  
 MSDS Information: 1-913-422-1888 ext 2305  
 MSDS Contact: Regulatory Compliance  
 email: [regcomp@nazdar.com](mailto:regcomp@nazdar.com)

## 2. HAZARDS IDENTIFICATION

*This product is a preparation. Health hazard information is based on its components.*

**Appearance** Water-white  
**Flammable Properties** Combustible liquid and vapor.  
**Emergency Overview** Irritant. May cause drowsiness and dizziness.

**Eyes** Severe eye irritant. The liquid splashed in the eyes may cause irritation and reversible damage.

**Skin** May cause skin irritation and/or dermatitis. May be absorbed through the skin in harmful amounts.

**Inhalation** May cause irritation of respiratory tract. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Ingestion** Harmful if swallowed. Potential for aspiration if swallowed. Risk of serious damage to the lungs (by aspiration).

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Naphtha (petroleum), heavy aromatic	64742-94-5	10 - 30
1-Methyl-2-pyrrolidone	872-50-4	10 - 30
Dipropylene glycol monomethyl ether acetate	88917-22-0	10 - 30
Dimethyl Glutarate	1119-40-0	10 - 30
D-Limonene	5989-27-5	10 - 30
Polyethylene glycol octylphenyl ether	9036-19-5	5 - 10
Dimethyl Adipate	627-93-0	1 - 5
Dimethyl Succinate	106-65-0	1 - 5
Naphthalene (contaminant)	91-20-3	1 - 5
1,2,4-Trimethylbenzene (contaminant)	95-63-6	< 0.5

• Component names which have the word (contaminant) are constituents contained in Aromatic Hydrocarbon ingredients and are an integral part of the ingredient and cannot be separated. The percentage listed for the contaminant is as contained in the Hydrocarbon ingredient. (Example: 100% Hydrocarbon, 10% Contaminant A, 3% Contaminant B)

## 4. FIRST AID MEASURES

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

<b>Skin Contact</b>	Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.
<b>Inhalation</b>	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

**5. FIRE-FIGHTING MEASURES**

<b>Flammable Properties</b>	Combustible liquid and vapor.
<b>Suitable Extinguishing Media</b>	Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Cool containers / tanks with water spray. Fire or intense heat may cause violent rupture of packages.
<b>Specific Hazards Arising from the Chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions</b>	Remove all sources of ignition. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
<b>Methods for Cleaning Up</b>	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools.
<b>Environmental Precautions</b>	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Do not take internally. Harmful or fatal if swallowed. Take notice of the directions of use on the label.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Keep away from heat and sources of ignition.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Ontario TWAEV	Mexico OEL (TWA)
1-Methyl-2-pyrrolidone				TWA: 400 mg/m <sup>3</sup>	



Dipropylene glycol monomethyl ether acetate				TWA: 100 ppm TWA: 776 mg/m <sup>3</sup> STEL: 150 ppm STEL: 1164 mg/m <sup>3</sup>	
Naphthalene (contaminant)	TWA: 10 ppm STEL: 15 ppm Skin	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>	250 ppm	TWA: 10 ppm STEL: 15 ppm Skin	TWA/LMPE-PPT: 10 ppm TWA/LMPE-PPT: 50 mg/m <sup>3</sup> STEL/LMPE-CT: 15 ppm STEL/LMPE-CT: 75 mg/m <sup>3</sup>

**Engineering Measures**

Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.

**Personal Protective Equipment**

**Respiratory Protection**

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.

**Eye Protection**

Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.

**Skin Protection**

Wear protective gloves/clothing. Solvent-resistant apron and boots.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Water-white	<b>Physical State</b>	Liquid
<b>Odor</b>	Characteristic	<b>Odor Threshold</b>	No information available
<b>pH</b>	No information available	<b>Autoignition Temperature</b>	No information available
<b>Boiling point/Boiling Range</b>	>149 °C / >300 °F	<b>Melting Point/Range</b>	No information available
<b>Freezing Point/Range</b>	No information available	<b>Solubility</b>	No information available
<b>Evaporation Rate</b>	No information available	<b>Partition Coefficient (n-octanol/water)</b>	No information available
<b>Vapour Pressure</b>	No information available	<b>Vapour Density</b>	Heavier than air
<b>Flammability (solid, gas)</b>	No information available	<b>Flammability Limits in Air</b>	
		Upper No information available	
		Lower No information available	
<b>Flash Point</b>	64 °C / 148 °F	<b>Photochemically Reactive</b>	Yes
<b>Method</b>	Pensky Martens Closed Cup (PMCC)		
<b>Weight Per Gallon (lbs/gal)</b>	8.15	<b>Specific Gravity</b>	0.98
<b>VOC by weight %</b>	92	<b>VOC by volume %</b>	92.65
<b>VOC lbs/gal (less water)</b>	7.5	<b>VOC grams/liter (less water)</b>	898.81

**10. STABILITY AND REACTIVITY**

<b>Chemical Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Incompatible Products</b>	Strong acids. Strong bases. Strong oxidizing agents. Reducing agents.
<b>Hazardous Decomposition Products</b>	Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), heavy aromatic	>5000 mg/kg ( Rat )	>2000 mg/kg ( Rabbit )	>590 mg/m <sup>3</sup> ( Rat ) 4 h
1-Methyl-2-pyrrolidone	3598 mg/kg ( Rat )	>5000 mg/kg ( Rabbit ) 2500 mg/kg ( Rat )	3.1 mg/L ( Rat ) 4 h
Dimethyl Glutarate	8191 mg/kg ( Rat )		>5.6 mg/L ( Rat ) 4 h
D-Limonene	4400 mg/kg ( Rat )	>2000 mg/kg ( Rabbit )	
Polyethylene glycol octylphenyl ether	4190 mg/kg ( Rat )		
Dimethyl Adipate	1920 mg/kg ( Rat )		
Dimethyl Succinate	>5000 mg/kg ( Rat )	>5000 mg/kg ( Rabbit )	
Naphthalene (contaminant)	490 mg/kg ( Rat )	>2500 mg/kg ( Rat ) >20 g/kg ( Rabbit )	>340 mg/m <sup>3</sup> ( Rat ) 1 h
1,2,4-Trimethylbenzene (contaminant)	3400 mg/kg ( Rat )	>3160 mg/kg ( Rabbit )	18 g/m <sup>3</sup> ( Rat ) 4 h

### Chronic Toxicity

Component	ACGIH	IARC	NTP	OSHA
Naphthalene (contaminant)		Group 2B	Reasonably Anticipated	X

**IARC:** (International Agency for Research on Cancer)

**NTP:** (National Toxicity Program)

**OSHA:** (Occupational Safety & Health Administration)

Group 2B - Possibly Carcinogenic to Humans

Reasonably Anticipated to be a Human Carcinogen

X - Present

### Sensitisation

No information available

### Mutagenic Effects

No information available

### Reproductive Effects

No information available

### Developmental hazard

No information available

### Teratogenicity

No information available

### Chronic Effects

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Blood, Central nervous system, Eyes, Kidney, Liver, Skin.

### Target Organ Effects

Blood, Central nervous system, Eyes, Kidney, Liver, Skin.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

Component	Algae	Fish	Water Flea
Naphtha (petroleum), heavy aromatic		96h LC50 <i>Lepomis macrochirus</i> : 1740 mg/L [static] 96h LC50 <i>Pimephales promelas</i> : 19 mg/L [static] 96h LC50 <i>Pimephales promelas</i> : 41 mg/L 96h LC50 <i>Pimephales promelas</i> : 45 mg/L [flow-through]	



1-Methyl-2-pyrrolidone	72h EC50 <i>Desmodemus subspicatus</i> : >500 mg/L	96h LC50 <i>Pimephales promelas</i> : 1072 mg/L [static] 96h LC50 <i>Poecilia reticulata</i> : 1400 mg/L [static] 96h LC50 <i>Leuciscus idus</i> : 4000 mg/L [static] 96h LC50 <i>Lepomis macrochirus</i> : 832 mg/L [static]	48h EC50 <i>Daphnia magna</i> : 4897 mg/L
Dimethyl Glutarate		96h LC50 <i>Pimephales promelas</i> : 19.6 - 26.2 mg/L [static]	48h EC50 <i>Daphnia magna</i> : 122.1 - 163.5 mg/L
D-Limonene		96h LC50 <i>Pimephales promelas</i> : 0.619 - 0.796 mg/L [flow-through] 96h LC50 <i>Oncorhynchus mykiss</i> : 35 mg/L	
Dimethyl Succinate		96h LC50 <i>Brachydanio rerio</i> : 50 - 100 mg/L [static]	
Naphthalene (contaminant)	72h EC50 <i>Skeletonema costatum</i> : 0.4 mg/L	96h LC50 <i>Oncorhynchus mykiss</i> : 0.91 - 2.82 mg/L [static] 96h LC50 <i>Pimephales promelas</i> : 5.74 - 6.44 mg/L [flow-through] 96h LC50 <i>Oncorhynchus mykiss</i> : 1.6 mg/L [flow-through] 96h LC50 <i>Pimephales promelas</i> : 1.99 mg/L [static] 96h LC50 <i>Lepomis macrochirus</i> : 31.0265 mg/L [static]	48h EC50 <i>Daphnia magna</i> : 1.09 - 3.4 mg/L [static] 48h EC50 <i>Daphnia magna</i> : 1.96 mg/L [Flow through] 48h LC50 <i>Daphnia magna</i> : 2.16 mg/L
1,2,4-Trimethylbenzene (contaminant)		96h LC50 <i>Pimephales promelas</i> : 7.19 - 8.28 mg/L [flow-through]	48h EC50 <i>Daphnia magna</i> : 6.14 mg/L

**Persistence and Degradability** No information available  
**Bioaccumulation** No information available  
**Mobility in Environmental Media** No information available

Component	log Pow
Naphtha (petroleum), heavy aromatic	4.5
1-Methyl-2-pyrrolidone	-0.46
Dimethyl Succinate	0.19
Naphthalene (contaminant)	3.3
1,2,4-Trimethylbenzene (contaminant)	3.63

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** Dispose of contents/container in accordance with local regulation.  
**Contaminated Packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT** Printing Ink Related Material, Liquid, Not Regulated  
**ICAO/IATA** Not classified as dangerous in the meaning of transport regulations  
**IMDG/IMO** Not classified as dangerous in the meaning of transport regulations

### 15. REGULATORY INFORMATION

**International Inventories**  
 Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

**U.S. Federal Regulations****SARA 313**

The following components are subject to reporting levels established by SARA Title III, Section 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
1-Methyl-2-pyrrolidone	872-50-4	10 - 30	1.0
Naphthalene (contaminant)	91-20-3	1 - 5	0.1

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

Component	CAS-No	Weight %
Naphthalene (contaminant)	91-20-3	1 - 5

**U.S. State Regulations**

Component	Massachusetts Right To Know	Minnesota Right To Know	New Jersey Right To Know	Pennsylvania Right To Know
1-Methyl-2-pyrrolidone	X	Not Listed	X	X
Naphthalene (contaminant)	X	X	X	X
1,2,4-Trimethylbenzene (contaminant)	X	X	X	X

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer and / or WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm

Component	CAS-No	Weight %
1-Methyl-2-pyrrolidone	872-50-4	10 - 30
Naphthalene (contaminant)	91-20-3	1 - 5

**Canada**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

Component	WHMIS Classifications of Components
1-Methyl-2-pyrrolidone	B3,D2B
D-Limonene	B3,D2B
Polyethylene glycol octylphenyl ether	D2B
Naphthalene (contaminant)	B4,D2A
1,2,4-Trimethylbenzene (contaminant)	B3

Component	NPRI - National Pollutant Release Inventory
Naphtha (petroleum), heavy aromatic	Part 5 Substance Part 5, Other Groups and Mixtures
1-Methyl-2-pyrrolidone	Part 4 Substance Part 1, Group 1 Substance
Dimethyl Glutarate	Part 4 Substance
D-Limonene	Part 5 Substance Part 5, Individual Substance
Polyethylene glycol octylphenyl ether	Part 1, Group 1 Substance
Dimethyl Adipate	Part 4 Substance
Dimethyl Succinate	Part 4 Substance
Naphthalene (contaminant)	Part 1, Group 1 Substance
1,2,4-Trimethylbenzene (contaminant)	Part 4 Substance Part 1, Group 1 Substance Part 5, Individual Substance

**Regulation (EC) No. 1907/2006 (REACH), Article 57**

This product contains substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57)

Component	CAS-No	Weight %
1-Methyl-2-pyrrolidone	872-50-4	10 - 30

---

HMIS:	Health 2 *	Flammability 2	Reactivity 0	PPE X
-------	---------------	-------------------	-----------------	----------

**16. OTHER INFORMATION**

Revision Date Aug-27-2012

Revision Note New MSDS format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of MSDS

