



Innovative Signs & Safety Solutions

Home | Order Status | Register | View

Search **Item Number**

GO

1-800-4

Regulation Resource Site

On-Line Catalog | Site Home | MSDS | CFR | Safety Resources |

MSDS Database

Search Resource Site **All**

GO

Most Po
in Hazard

- ▶ [Chemical Haza](#)
- ▶ [Diamond Pane](#)
- ▶ [Diamond Pane Yourself](#)
- ▶ [Panel Characte](#)
- ▶ [Chemical Haza](#)

Material Safety Data Sheet

Name E-Z PAINT THINNER
Company E.E.ZIMMERMAN COMPANY

MSDS cftdk
FSC 8010

MSDS Safety Information

FSC: 8010
MSDS Date: 08/26/1992
MSDS Num: CFTDK
LIIN: 00D007084
Product ID: E-Z PAINT THINNER
MFN: 01
Responsible Party
Cage: EEZIM
Name: E.E.ZIMMERMAN COMPANY
Box: 111254
City: PITTSBURGH PA 15238
Info Phone Number: 412-963-0949
Emergency Phone Number: 412-963-0949
Preparer's Name: UNKNOWN
Review Ind: Y
Published: Y

Fast F

- ▶ [Confined Spac](#)
- ▶ [Lockout Check](#)
- ▶ [CFR - 1910 L Fire Protector](#)
- ▶ [Asbestos Fact](#)
- ▶ [Traffic Signs](#)
- ▶ [Parking Signs](#)
- ▶ [Industrial Sign](#)
- ▶ [Tags](#)

Contractor Summary

Cage: EEZIM
Name: E.E.ZIMMERMAN COMPANY
Address: UNKNOWN
City: UNKNOWN NK 00000
Phone: UNKNOWN

Ingredients

Cas: 8052-41-3
RTECS #: WJ8925000
Name: STODDARD SOLVENT (WHICH IS THE PRINCIPAL INGREDIENT AND CONTAINS INGRED #2)
% Wt: 100%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM; 9596

Cas: 95-63-6
RTECS #: DC3325000
Name: 1,2,4-TRIMETHYLBENZENE (SARA 313)
% Wt: UNKNOWN
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 25 PPM
ACGIH TLV: 25 PPM; 9596

Health Hazards Data

LD50 LC50 Mixture: LD50 ORAL RAT HAS NOT BEEN ESTABLISHED
Route Of Entry Inds - Inhalation: YES



Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EYES:MAY CAUSE IRRITATION.SKIN:MAY CAUSE IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION AND CNS DEPRESSION.INGEST:MAY CAUSE GASTROINTESTINAL IRRITATION.ASPIRATION HAZARD.
Explanation Of Carcinogenicity: THIS ITEM DOES NOT CONTAIN ANY INGREDIENT AT 0.1% OR GREATER WHICH IS A CARCINOGEN.
Signs And Symptions Of Overexposure:
INHAL:DIZZINESS.SKIN:DERMATITIS.INGEST:NAUSEA.
Medical Cond Aggravated By Exposure: PERSON WITH PREEXISTING DISEASE OF THE SKIN,EYE AND RESPIRATORY SYSTEM MAY BE AT INCREASED RISK FROM EXPOSURE TO THIS ITEM.
First Aid: EYES:FLUSH WITH WATER UNTIL ALL TRACES OF THIS MATERIAL ARE GONE.SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS.SKIN:REMOVE CONTAMINATED CLOTHING.WASH WITH SOAP AND WATER.INHAL:REMOVE FROM EXPOSURE.GIV E OXYGEN OR ARTIFICIAL RESPIRATION IF NESCESSARY.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.

Handling and Disposal

Spill Release Procedures: ELIM SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.SOAK UP WITH AN INERT,NON-COMBUSTIBLE ABSORBANT.WASH SPILL AREA.
Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.
Handling And Storage Precautions: STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.AVOID HEAT,SPARKS AND FLAMES.
Other Precautions: AVOID EYE AND SKIN CONTACT.DO NOT INHALE VAPORS.

Fire and Explosion Hazard Information

Flash Point Method: TCC
Flash Point Text: 100F,43C
Lower Limits: 1
Upper Limits: 7
Extinguishing Media: WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.
Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.
Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MFR.

Control Measures

Respiratory Protection: USE A NIOSH-MSHA APPROVED RESPIRATOR FOR BOTH ORGANIC VAPORS AND PARTICULATE DUST.
Ventilation: USE LOCAL EXHAUST AT THE WORKSITE;GENERAL EXHAUST TO MAINTAIN TLV/PEL.
Protective Gloves: NEOPRENE
Eye Protection: CHEMICAL SPLASH GOGGLES.
Other Protective Equipment: APRON,COVERALLS.PROVIDE A LOCAL EYE WASH STATION AND QUICK DRENCH SHOWER.
Work Hygienic Practices: USE REASONABLE CARE WITH THIS ITEM.WASH HANDS BEFORE EATING.
Supplemental Safety and Health: NONE

Physical/Chemical Properties

HCC: F4
B.P. Text: ANDgt;309F,ANDgt;154C
Decomp Text: UNKNOWN
Vapor Pres: 3
Vapor Density: 4.85
Spec Gravity: 0.77
Viscosity: ANDlt;100SUS@100F
Evaporation Rate ANDamp; Reference: 0.2 (N-BUTYL ACETATE=1)

Solubility in Water: NEGLIGIBLE
Appearance and Odor: COLORLESS LIQUID WITH MILD PETROLEUM ODOR.
Percent Volatiles by Volume: 100
Corrosion Rate: UNKNOWN

Reactivity Data

Stability Indicator: YES
Stability Condition To Avoid: HIGH HEAT AND SOURCES OF IGNITION.
Materials To Avoid: NONE SPECIFIED BY MFR.
Hazardous Decomposition Products: NONE SPECIFIED BY MFR.
Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Code: EEZIM
Trans ID NO: 6882
Product ID: E-Z PAINT THINNER
MSDS Prepared Date: 08/26/1992
Review Date: 12/05/1997
MFN: 1
Net Unit Weight: 32.1 LBS
AF MMAC Code: NR
Multiple KIT Number: 0
Review IND: Y
Additional Data: NONE

Detail DOT Information

DOT PSN Code: LFE
DOT Proper Shipping Name: PAINT
DOT PSN Modifier: INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS,
VARNISH, POLISH, LIQUID FILLER, AND LIQUID LACQUER BASE
Hazard Class: 3
UN ID Num: UN1263
DOT Packaging Group: III
Label: FLAMMABLE LIQUID
Special Provision: B1,B52,T7,T30
Packaging Exception: 150
Non Bulk Pack: 173
Bulk Pack: 242
Max Qty Pass: 60 L
Max Qty Cargo: 220 L
Vessel Stow Req: E,B,A

Detail IMO Information

IMO PSN Code: LCT
IMO Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL
IMO PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS,
VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT
THINNING OR REDUCING COMPOUND) o
IMDG Page Number: 3372
UN Number: 1263

UN Hazard Class: 3.3
IMO Packaging Group: III
Subsidiary Risk Label: -
EMS Number: 3-05
MED First Aid Guide NUM: 310

Detail IATA Information

IATA PSN Code: SXH
IATA UN ID Num: 1263
IATA Proper Shipping Name: PAINT
IATA PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC, VARNISH,
POLISH, LIQUID FILLER AND LIQUID LACQUER BASE)
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: III
Packing Note Passenger: 309
Max Quant Pass: 60L
Max Quant Cargo: 220L
Packaging Note Cargo: 310

Detail AFI Information

AFI PSN Code: SXH
AFI Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL
AFI PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS,
VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT
THINNING OR REDUCING COMPOUNDS)
AFI Hazard Class: 3
AFI UN ID NUM: UN1263
AFI Packing Group: III
Special Provisions: P5
Back Pack Reference: A7.3

HAZCOM Label

Product ID: E-Z PAINT THINNER
Cage: EEZIM
Company Name: E.E.ZIMMERMAN COMPANY
Street: UNKNOWN
City: UNKNOWN NK
Zipcode: 00000
Health Emergency Phone: 412-963-0949
Label Required IND: Y
Date Of Label Review: 12/05/1997
Status Code: C
MFG Label NO: UNKNOWN
Label Date: 12/05/1997
Year Procured: 1997
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Slight
Reactivity Hazard: None
Hazard And Precautions: EYES:MAY CAUSE IRRITATION.SKIN:MAY CAUSE
IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION AND CNS
DEPRESSION.INGEST:MAY CAUSE GASTROINTESTINAL IRRITATION.ASPIRATION HAZARD.
STORE IN A COOL, DRY, WELL-V ENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN
USE.AVOID HEAT, SPARKS AND FLAMES. FIRST AID: EYES:FLUSH WITH WATER UNTIL ALL
TRACES OF THIS MATERIAL ARE GONE.SEEK MEDICAL ATTENTION IF IRRITATION PER
SISTS.SKIN:REMOVE CONTAMINATED CLOTHING.WASH WITH SOAP AND WATER.INHAL:REMOVE
FROM EXPOSURE.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY.INGEST:DO
NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDIC AL ATTENTION.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.

[About](#) | [Contact emedco](#) | [Catalog Request](#)
[Jobs](#) | [Links](#) | [Privacy Statement](#)

©Copyri
800-442-36:
FAX 800-344-25
/